

## SGP溶協・高炉

| 呼び径 |            | 外径<br>(mm) | 溶協         |    | 高炉         |    |
|-----|------------|------------|------------|----|------------|----|
| A   | B<br>(インチ) |            | 厚さ<br>(mm) | 在庫 | 厚さ<br>(mm) | 在庫 |
| 15  | 1/2        | 21.7       | 2.8        | ●  | 2.8        | ●  |
| 20  | 3/4        | 27.2       | 2.8        | ●  | 2.8        | ●  |
| 25  | 1          | 34.0       | 3.2        | ●  | 3.2        | ●  |
| 32  | 1 1/4      | 42.7       | 3.5        | ●  | 3.5        | ●  |
| 40  | 1 1/2      | 48.6       | 3.5        | ●  | 3.5        | ●  |
| 50  | 2          | 60.5       | 3.8        | ●  | 3.8        | ●  |
| 65  | 2 1/2      | 76.3       | 4.2        | ●  | 4.2        | ●  |
| 80  | 3          | 89.1       | 4.2        | ●  | 4.2        | ●  |
| 90  | 3 1/2      | 101.6      | 4.2        | ●  | 4.2        | ●  |
| 100 | 4          | 114.3      | 4.5        | ●  | 4.5        | ●  |
| 125 | 5          | 139.8      | 4.5        | ●  | 4.5        | ●  |
| 150 | 6          | 165.2      | 5.0        | ●  | 5.0        | ●  |
| 175 |            | 190.7      | 5.3        | ●  | 5.3        | ●  |
| 200 | 8          | 216.3      | 5.8        | ●  | 5.8        | ●  |
| 225 |            | 241.8      |            |    | 6.2        | ●  |
| 250 | 10         | 267.4      | 6.6        | ●  | 6.6        | ●  |
| 300 | 12         | 318.5      | 6.9        | ●  | 6.9        | ●  |
| 350 | 14         | 355.6      | 7.9        | ●  | 7.9        | ●  |
| 400 | 16         | 406.4      | 7.9        | ●  | 7.9        | ●  |
| 450 | 18         | 457.2      |            |    | 7.9        | ●  |
| 500 | 20         | 508.0      |            |    | 7.9        | ●  |

※ 溶協 6A、8A、10Aは、取り寄せ材になります。